KENWOOD

UHF FM TRANSCEIVER PKT-23

PMR446 License Free Radio Success in you PocKeT **ProTalk**ilt

- KNB-71L Li-ion Battery (3.8 V/1,430 mAh)
- KSC-44CR Fast Charger
- KSC-44SL AC adapter single
- KBH-20 Spring Action Belt Clip
 - Owner's Manual

OPTION

*Available later







KBH-20 Spring Action Belt Clip







KSC-44SL* AC Adapter Single

KSC-44ML* AC Adapter Multiple

KNB-71L Li-ion Battery (3.8 V/1,430 mAh)



KHS-33 Earbud In-line PTT Headset (Single Pin Jack)



KHS-34 C-Ring In-line PTT Headset (Single Pin Jack)

SPECIFICATIONS

NODEL	PKT-23E		
GENERAL			
Frequency Range	446.0 to 446.1 MHz		
Number of Channels	Max. 8		
Channel Spacing (Narrow)	12.5 KHz		
Battery Voltage	3.8 V DC ± 10 %		
Battery Life (5-5-90)*	Approx. 15 hrs		
Frequency Stability	+/-2.5 ppm		
Dimensions (Excluding antenna)	W46.0 x H85.0 x D21.0 mm		
Weight with battery	Approx. 110 g		
RECEIVER			
Sensitivity (Narrow) EN 20dB SINAD	-7.0 dBμV		
Selectivity (Narrow)	60 dB		
Intermodulation Distortion (Narrow)	60 dB		
Audio Distortion	Less than 5 %		
Audio Output (Internal)	300 mW/4 Ω		
Audio Output (External)	2 mW/32 Ω		
TRANSMITTER			
RF Power Output	ERP 500 mW		
Spurious Response	-36 dBm ≤ 1 GHz, -30 dBm > 1 GHz		
FM Hum & Noise (Narrow)	50 dB		
Modulation Distortion	Less than 5 %		
Type of Emission	8K50F3E		

^{*}Based upon 5 % transmit/ 5 % receive/ 90 % standby (standard duty cycle)

Kenwood Electronics UK Limited

12 Priestley Way, London, NW2 7BA, United Kingdom

www.kenwoodcommunications.co.uk





The PKT-23. An easy-to-use, license-free PMR446 UHF FM transceiver. Thin, lightweight and durable. Compliant with IP54 and 11 US MIL-STD standards.

Small

At **110 g**, it is the smallest & lightest 2-Way Radio from KENWOOD.

Simple

Simple and license-free operation in an all-in-one package ready for immediate use.

Tough

Complies with **IP54** (dust/water resistant) and durability meeting or exceeding **MIL-STD** 810 C/D/E/F/G **11 items**.

Powerful

500 mWatts Transmit Power. Up to **15 hours** of operation. (5-5-90; battery saver ON)







Built Business Tough

Meets MIL-STD and IP54

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/ I	50 0.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II
Temperature Shock	503.1/ I	503.2/1	503.3/ I	503.4/ I, II	503.5/ I
Solar Radiation	505.1/ I	505.2/1	505.3/ I	505.4/ I	505.5/ I
Rain	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III
Humidity	507.1/ I, II	507.2/ II, III	507.3/ II, III	507.4	507.5/ II
Salt Fog	509.1/ I	509.2/1	509.3/ I	509.4	509.5
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I
Shock	516.2/ I, II, V	516.3/ I, IV	516.4/ I, IV	516.5/ I, IV	516.6/ I, IV
International Protection Standard					
Duet & Water Pr	otootion	IDE/			

Built-in 3.5D Jack

Connect the KHS-33 or KHS-34 headphone for better use in noisy environments or for private conversations.



*Headphones and earphones are not supplied with the unit.

Built-in VOX

Built-in VOX allows hand free operation which automatically starts transmission in response to your voice when using an external microphone.

Equipped with Micro USB terminal

The standard micro USB port means a smart phone charger can also be used to charge the PKT-23.



Self Programing

User selectable channel frequencies, QT tones, and DQT codes without using an FPU(programming software).





Easy Communication

Light Weight and Simple Operation

Fitting in the palm of your hand, the PKT-23 is easy to take anywhere your staff needs to go. At only 110 g, it can fit comfortably in a pocket or attached with the included belt clip. The front panel button layout makes the PKT-23 easy to operate.



500 mW Transmit Power with Up to 15 Hours of Operation

The PKT-23 offers 500 mWatts of power, for direct radio-to-radio communication on the same frequency. The built-in 1,430 mAh lithium-ion battery provides up to 15 hours of use.

Battery life		
Battery life (5-5-90 duty cycle)	Saver on: 15 hours	
	Saver off: 11 hours	
Battery charging time	2 hours	

8 Channels with Voice Guide

The PKT-23 provides up to 8 channels, allowing you to assign channels to specific team members. The Voice Guide alerts you when you change channels.



Calling Alert

You are alerted to an incoming call by the flashing LED light and a beep.



Multi-coloured LED

Blinking LED lights in 3 colours indicate the PKT-23's transmission status and low battery status.







ProTalk LT UHF FM TRANSCEIVER PKT-23

PMR446 **License Free Radio**

Actual size

W: 46 mm H: 85 mm

D: 21 mm

*Excluding antenna.